

A

B

C

D

仕様 SPECIFICATIONS	
口金の開き	0~303mm
締付トルク	
TIGHTENING TORQUE	
締付けレンジ	0 10KN
CLAMP RANGE	1 20KN
	2 32KN
	3 45KN
製品質量	
MASS OF POWER VISE	95kg

(吊りボルト用)
(EYE BOLT)

2×5-M10 深さ20
DEPTH

2×2-M10 深さ20
DEPTH

2×2-M10

六角穴付ボルト
M16×65
HEX. SOCKET HEAD
CAP SCREW

(押さえ金具4セット付属)
(CLAMPING PARTS ACCESSARY 4 PAIR)

図面に記入のない寸法の一 般公差			
寸法区分 mm	切削加工 穴明中心	板金加工 製造加工	鍛造品
1以上 4以下	±0.1	±0.3	±0.5
4を超え 16	±0.2	±0.5	±0.7
16 63	±0.3	±0.7	±0.9
63 250	±0.5	±1.2	±1.5
250 1000	±0.8	±2.0	±2.5
1000 2000	±1.0	±2.5	±3.5
2000 5000	±1.5	±3.5	±5.0

注 記 NOTE

- 1) 0レンジは増力機構なしの締付となりますので締付力は許容量を示します。
0-RANGE MEANS CLAMP THAT THERE IS NO A FORCE
INCREASING MECHANISM.
CLAMPING FORCE SHOWS AN ALLOWANCE VALUE.

CUSTOMER		
MOD. NO.	D A T E	REASON OF REVISION
1	25.09.04	ADJUSTMENT(Δ8 PLACES)

CAREER	61M3523731		SCALE	TYPE	VE200N	WEIGHT	kg
		3:10		NAME	パワーバイス POWER VISE		
MANAGER	CHIEF		DRAWN BY N. SA NADA		VE200N ガイキ VE200N OUTSIDE VIEW		
KITAGAWA IRON WORKS CO.,LTD.		DATE 07.09.27	3RD ANGLE 	DRW NO.	61M	39	6433
							