



UNIT : mm

SPEC Model	Matching Adapter	Bar Capacity (mm)	Sleeve Stroke (mm)	Max. Push Force KN(kgf)	Max. Gripping Force KN(kgf)	Max. Speed (r.p.m.)	Weight (kg)
CR42-140	140	42	7	25 (2549)	55 (5608)	6000	6.2
CR60-170	170	60	7	30 (3059)	65 (6628)	5000	11.5
CR60-220	220	60	7	30 (3059)	65 (6628)	5000	15.5

DIM Model	A (h6)	B	C	D	E	F (h6)	G	H	J max.	K	L	M	N	P	T
CR42-140	155	114	100	23	104.78	140	M66xP1.5	60	M55xP2.0	25	18	6	11.9	3-M10	3.1
CR60-170	185	139	130	30	133.35	170	M90xP1.5	80	M74xP2.0	30	18	6	17.9	6-M12	3.1
CR60-220	235	141	130	32	171.45	220	M90xP1.5	80	M74xP2.0	30	20	6	19.9	6-M16	3.1

UNIT : mm

SPEC Model	Matching Spindle	Bar Capacity (mm)	Sleeve Stroke (mm)	Max. Push Force KN(kgf)	Max. Gripping Force KN(kgf)	Max. Speed (r.p.m.)	Weight (kg)
CR26A4	A2-4	26	5	20 (2039)	44 (4486)	7000	4.5
CR30A4	A2-4	30	5	20 (2039)	44 (4486)	7000	4.1
CR42A5	A2-5	42	7	25 (2549)	55 (5608)	6000	6.2
CR42A6	A2-6	42	7	25 (2549)	55 (5608)	6000	8.2
CR60A6	A2-6	60	7	30 (3059)	65 (6628)	5000	13
CR80A8	A2-8	80	7	35 (3568)	73 (7443)	4000	21

DIM Model	A	B	C	D	E	F	G	H	J max.	K	N	P	T
CR26A4	112	103.5	85	30	82.55	63.513	M50xP1.5	45	M40xP1.5	15	21.7	3-M10	2.3
CR30A4	112	103.5	85	30	82.55	63.513	M50xP1.5	45	M40xP1.5	15	21.7	3-M10	2.3
CR42A5	135	124	100	27	104.78	82.563	M66xP1.5	60	M55xP2.0	25	27.4	4-M10	3.1
CR42A6	170	124	100	32	133.35	106.375	M66xP1.5	66	M60xP2.0	22	27.4	4-M12	3.1
CR60A6	170	145	130	27	133.35	106.375	M90xP1.5	80	M74xP2.0	30	29.9	4-M12	3.1